

	<b>RAV.IO / RAV.SRC.IO*</b>	<b>DANTE.IO / DANTE.SRC.IO*</b>	<b>SG.IO*</b>
<b>Network</b>			
Protocol	RAVENNA	Dante	SoundGrid
Network-Layer	3	3	2
Number of channels (1 FS / 2 FS / 4 FS)	128 / 64 / 32	64 / 32 / 16	128 / 64 / –
Number of streams	32	32	
Standards	AES67 ST 2110-30 / 31	AES67 ST 2110-30**	
<b>Signal</b>			
Sample Rates	44.1 kHz up to 192 kHz	44.1 kHz up to 192 kHz	44.1 kHz up to 96 kHz
Sample Rate Conversion	RAV.SRC.IO	DANTE.SRC.IO	
<b>Control</b>			
web gui	yes	yes	no
globcon	yes	no	no
software application	ANEMAN*	Dante Controller	SoundGrid Studio
<b>Interfaces</b>			
RJ45 Gigabit Ethernet	2	2	2
SFP	1	1	1
<b>Features</b>			
WAN capability	yes (> 500 ms delay)	no	no
Stream Redundancy	yes ST 2022-7	primary / secondary	no
Switch Configuration	yes	yes	no
Out-of-band management	yes	no	no
PTP Hybrid Mode	yes	yes	no
Discovery	RTSP, SAP	SAP	--

\* not available at this time

\*\* only with Dante Domain Manager